

CVTM

Features

- ✓ 1.6 m cutting width
- ✓ Shaft Driven
- ✓ 32 Scoop flails
- ✓ 115 mm Roller



Bomford Toppers

BOMFORD

Developed to meet the demands of local authorities for parks and municipal areas, The CVTM has a cutting width of 1.6m variable cutting height from 8mm to 130mm, a mountable kerb height of 355mm, sealed bearings pressed scoop (Gamma) flails and weighs in at 300kgs. The new Bomford CVTM has twin V belt drive and has interchangeable mounting arms to accommodate a large range of prime movers.

	CVTM
Cutting width	1600mm
Overall width	1807mm
Max cutting height	130mm
Min cutting height	8mm
Weight	300Kg
Mountable kerb height	(with NH MC35) 14 inches
Front wheels	300mm diameter 105mm width
Rear roller	115mm diameter
Rotor shaft	102mm diameter
Bearing	40mm sealed bearings
Flails	32 scoop type / 48 metres per second tip speed
Gearbox and tube	EP90 filled gearbox and drive tube / Quad bearings
PTP	2000 rpm PTO input speed (different input speeds can be catered for)
Cowl	4mm Domex sheet, 5mm rear rubber guarding, heavy duty arms and Cat 2 pins
Drive	twin vee-belts on cast pulleys, tensioned through gearbox mountings

