

TurboMower Elite / Euro

Features

- ✓ 1.3m, 1.5m, 1.9m, 2.25m, 2.45m and 2.7m cutting widths
- ✓ Front mount option
- ✓ Hydraulic or manual offset
- ✓ Over run slip clutch protected
- ✓ Cat II three point linkage mounted
- ✓ Standard fitted roller and side skids

The Turbo mower elite range offers operator's a huge choice of cutting widths at very cost effective prices.

	TME 1300	TME 1500	TME 1900	TME 2250	TME 2450	TME 2700	TurboEuro 250	TurboEuro 280
Working width	1.3m (4'3")	1.43m (4'9")	1.91m (6'3")	2.26m (7'5")	2.42m (8')	2.72m (8'10")	2.5m (8'3")	2.8m (9'2")
Weight	185kgs	205kgs	410kgs	462kgs	495/515 Combi	525/545 Combi	487kg	517kg
Hydraulic offset	-	-	Option	Option	Option	Option	Hydraulic Operation	Hydraulic Operation
Fully offset left of centre	68cm	75cm	150cm	110cm	172cm	201cm	400cm	400cm
PTO speed	540	540	540	540	540	1080	1000	1000
Front mount	NA	NA	NA	NA	Optional	Optional		
No of flails (Whale Tail)	18	20	24	28	30	34	28	32
Power requirements	35hp	35hp	45hp	55hp	65hp	75hp	60hp	80hp
Front mount							Optional	Optional

