

# Turbo VM

## Features

- ✓ 1.6m or 2.0m cutting widths
- ✓ Plus 90° to minus 50° cowl angling
- ✓ Direct drive through twin pivoting gearboxes
- ✓ 750mm offset
- ✓ Cat II three point linkage
- ✓ Front mountable



The Turbo VM is specifically designed for verge mowing over long sustained periods.

	VM1600	VM2000
Width	1.6m (5'4")	2.0m (6'7")
Fully offset left of centre	750mm (2'5")	750mm (2'5")
Direct Drive System	"Quad Power" Drive Belts + 90° Gearbox x2	"Quad Power" Drive Belts + 90° Gearbox x2
PTO input rpm	1000	1000
No. of flails	44	54
Tractor hp	90hp	125hp
Cowl Angle Movement	140° (+90° to -50°)	140° (+90° to -50°)
Weight	1180kg	1250kg
Front mountable	Optional	NA



# Bandit

## Features

- ✓ 1.5m, 1.8m or 2.25m cutting widths
- ✓ Fitted with roller as standard
- ✓ Variable cutting height
- ✓ Cat II three point linkage
- ✓ 540 or 1000 rpm PTO speeds

The Bandit trailed flail mower is aimed at professional users where efficiency and finish are a must. The Bomford Bandit mower range is built to withstand the toughest working conditions. Remaining manoeuvrable when mowing light up to walls and obstructions. The flexible design of the Bandit allows it to be front or rear mounted simply by turning the A frame around (except B1200).

	<b>B1500</b>	<b>B1800</b>	<b>B2250</b>
Cutting width	1.5m (4'11")	1.8m (6')	2.25m (7'2")
Transport width	1.74m (5'8")	2.05m (6'9")	2.50m (8'2")
Cutting height	13 - 105mm	13 - 105mm	13 - 105mm
No. of flails	40	50	62
Flail type	Choice	Choice	Choice
Offset system	Manual	Optional hydraulic	Hydraulic
Power requirement	30hp	50hp	90hp
Rear roller size	115mm	150mm	150mm
Weight	470kg	580kg	650kg

