

Kestrel Evo Power Plus

Introducing the Kestrel S 5.7P Power Plus. This new model release of the Kestrel now takes this popular reach arm mower to a new level with increased power and additional features.

These features include integral road lighting, tubular 3 point linkage and power slew with hydraulic breakout.

Key Features

- 5.7m reach
- 60hp gear pumps
- Parallel arm standard
- Choice of flails, heads and cutter bars
- Power slew
- Steel hose covers standard



Want to know more about the Kestrel Evo Power Plus range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard ○ Optional — Not Available

Kestrel Evo Power Plus	5.7m (18'8")
Tractor requirements	
Minimum horse power	60hp
Minimum weight	3500kg 7716lbs
Base unit mounting options	
Front mount	○
Mid-mount	—
Rear mount	●
Three point linkage (CAT II)	●
Axle bracket	—
Sub Frame	—
Yoke	—
Overall machine parameters	
Machine weight with head and oil	1210kg 2268lbs
Capacity of oil tank	160L 42.3usc
Weight of machine with oil but without head	970kg 2139lbs
Controls	
Cable Control (CC)	●
Low pressure hydraulics (LPH)	○
Electronic proportional control (EPP)	○
Intelligent control system (ICS)	—
Cable rotor reverse	○
Electronic rotor reverse	—
Hydraulic System	
System capability	54hp
Pump flow rate	88L 23.2usc
Pump type (Gear / Piston / Helical)	Gear
Pump arrangement (Twin / Tandem In-line)	Twin
Independent hydraulics	●
Oil cooler	○

Kestrel Evo Power Plus	5.7m (18'8")
Arm features and main frame	
Forward arm	—
Telescopic arm	—
Telescopic arm stroke	—
Power slew	●
Power slew angle	94°
Gravity breakout protection	—
Hydraulic breakout protection	●
Head float - manual operation	●
Head float - electronic operation	○
Left hand cutting	○
Right hand cutting	○
Left and right hand cutting	—
Arm attachments available	
Variable track bracket (VTB)	—
Sheartrim cutter bar	○
Pro-Saw	○
Ditch cleaner	—
Rotary head	○
Accessories	
Road lights	●
Debris blower	—
Warning arrow - Magnetic	○
Cab guard kit	●
Cutting heads (For Flail compatibility see page 95)	
1.2m Pro-Trim with 115/150mm roller	○
1.2m Pro-Trim ISMP with 115/150mm roller	○

Power slew and hydraulic breakout

For driver and machine safety.

Steel hose covers

Adding additional protection to drive motor houses.

Road lights & Oil cooler

Fitted as standard.



Parallel arm

Available as standard.

Working Reach

Head used for calcs: 1.2 Pro-Trim

	Kestrel Evo Power Plus 5.7m (18'8")
A	5.7m / 18'8"
B	5.9m / 19'4"
C	3.86m / 12'8"
D	5.1m / 16'9"
E	7.11m / 23'4"
X	1.3m / 4'1"
Y	1.0m / 3'4"

