

Tri-Blade

The Tri-Blade topper is of robust design and has three sets of newly designed, heavy duty timed blades for stripe free cutting.

With an adjustable cutting height of between 25mm (1") and 333mm (10") the Bomford Tri-Blade offers superb versatility.

Direct driven blades through 1000rpm independent gearboxes and rubber PTO shaft couplings protects against debris impact. Slip clutch protection on the PTO shaft ensures long life of the independent gearboxes.

Key Features

- 2.75m cutting width
- 3.0m transport width
- Variable cutting height
- Three sets of timed blades
- Slip clutch protection
- Front and rear heavy duty chain guards
- Cat II three point linkage
- 1000 rpm gearbox driven



Want to know more about the Tri-Blade range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/tri-blade/>



Product Specification

Tri-Blade	3000	4000
Cutting Width	2.75m / 9'	4m / 13'2"
Transport Width	3.0m / 9'10"	1.8m / 6'
Power Requirements	90hp	120hp
Length	3.54m / 11'4"	4.54m / 14'10"
Cutting Height	25mm-333mm / 1"-10"	25mm-333mm / 1"-10"
PTO Speed	1000rpm	1000rpm
Number Of Rotors	3	3
Number Of Blade Carriers	3	3
Number Of Blades	6	6
Number Of Skids	2	2
Weight	980kg / 2161lbs	1325kg / 2921lbs