



LANDSCAPE

Turbo Mower Offset

The Turbo Mower Offset range offers operators a choice of cutting widths at cost effective prices.

A well designed and constructed range, the Turbo Mower Offset is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

Proven Landscape Technology

Visit: www.bomford-turner.com



Turbo Mower Offset

Key Features

- 1.6m, 1.9m and 2.25m cutting widths
- Three-point linkage-mounting
- PTO overrun protection
- Choice of whale-tail or J flails
- 155 degrees of head movement
- Vertical and horizontal hydraulic adjustment
- Safety breakaway
- Double-skin protection
- Fuel-efficient, high-performance double spiral rotor
- Cutting height of 30mm - 80mm
- Maximum cutting diameter of 50mm
- Optional hydraulic floatation system



Hedge Cutting



Verge Cutting

| Product Specification | | 160 | 190 | 225 |
|---------------------------|---|-----------------|-----------------|-----------------|
| Cutting width | Maximum width of cut (m) | 1.6m (5'3") | 1.9m (6'3") | 2.25m (7'4") |
| HP requirement | Minimum hp requirement of tractor | 47-60 | 71-93 | 80-117 |
| Attachment | 3-Point Linkage (CAT II or III) | 3 Point Linkage | 3 Point Linkage | 3 Point Linkage |
| Weight | Weight of machine (kg) | 665 | 735 | 775 |
| PTO speed | Maximum RPM of PTO shaft | 540 | 540 | 540 |
| Number of flails | J flails on twisted shackle or back-to-back flail | 20 | 24 | 28 |
| Maximum downward movement | | -65° | -65° | -65° |
| Maximum upward movement | | +90° | +90° | +90° |

Bomford Turner Limited

Station Road, Salford Priors,
Nr. Evesham, Worcestershire
WR11 8SW, United Kingdom

Tel +44 (0) 1789 773383

Fax +44 (0) 1789 773238

E-mail info@bomford-turner.com



Visit: www.bomford-turner.com