

# Buzzard Evo Forward

The Buzzard Evo forward range has been specifically designed for the large scale contractor and agency.

With the added advantage of forward reach, give improved visibility for the operator along with a large choice in specification, and fully proportional controls.

## Key Features

- 7.25m or 8m reach
- 1.2m or 1.5m cutting heads
- Oil cooled as standard
- ICS fully proportional controls



**Want to know more about the Buzzard Evo Fwd range?**

Scan the QR code with a smart phone or tablet to instantly view the page.





### Impressive reach

3 arm design gives versatile reach characteristics for flexibility around obstacles.



### Transport position

Folding 3rd arm allows compact transport position.



### Powerful 74hp hydraulics

For continuous use. Twin pumps with separate oil tank.

## Product Specification

● Standard ○ Optional — Not Available

Buzzard Evo FWD	7.25m T (23'9")	8.0m T (26'3")
<b>Tractor requirements</b>		
Minimum horse power	120hp	140hp
Minimum weight	5500kg 12125lbs	6000kg 13228lbs
<b>Base unit mounting options</b>		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (Cat 11)	—	—
Axle bracket	●	●
<b>Overall machine parameters</b>		
Machine weight with head and oil	2290kg 5049lbs	2490kg 5490lbs
Capacity of oil tank	250L 66USG	250L 66USG
Weight of machine with oil but without head	2000kg 4409lbs	2200kg 4850lbs
<b>Controls</b>		
Cable Control (CC)	○	○
Low pressure hydraulics (LPH)	○	○
Electronic proportional control (EPP)	○	○
Intelligent control system (ICS)	●	●
Cable rotor reverse	—	—
Electronic rotor reverse	●	●
<b>Hydraulic system</b>		
System capability	74hp	74hp
Pump flow rate	125L 33USG	125L 33USG
Pump type (Gear/Piston/Helical)	Gear	Gear
Pump arrangement (Twin/In-line)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	●	●

Buzzard Evo FWD	7.25m T (23'9")	8.0m T (26'3")
<b>Arm features and main frame</b>		
Forward arm	1200mm 3'11"	1200mm 3'11"
Telescopic arm	●	●
Telescopic arm stroke	—	—
Power slew	●	●
Power slew angle	94°	94°
Gravity breakout protection	—	—
Hydraulic breakout protection	●	●
Arm float - manual operation	—	—
Arm float - electronic operation	●	●
Head float - manual operation	○	○
Head float - electronic operation	●	●
Left hand cutting	○	○
Right hand cutting	○	○
Left and right hand cutting	—	—
<b>Arm attachments available</b>		
Variable track bracket (VTB)	○	○
Sheartrim cutter bar	○	○
Pro-Saw	○	○
Ditch cleaner	○	○
Rotary head	○	○
<b>Accessories</b>		
Road Lights	●	●
Debris Blower	○	○
Cab Guard Kit	●	●
<b>Cutting heads (For Flail compatibility see page 97)</b>		
1.2m Pro-Cut - 115/150mm roller	●	●
1.5m Pro-Cut - 115/150mm roller	○	○
1.2m Pro-Cut ISMP - 115/150mm roller	○	○



### Forward reach position

Enables mid-mounted head position with simplicity of rear mounted arm.

## Working Reach

Head used for calcs: 1.2 Pro-Cut

	Buzzard Evo FWD 7.25m T (23'9")	Buzzard Evo FWD 8.0m T (26'3")
A	7.19m / 23'7"	7.94m / 26'1"
B	7.27m / 23'10"	8.13m / 26'8"
C	5.47m / 17'11"	6.31m / 20'8"
D	6.8m / 22'4"	7.4m / 24'3"
E	8.52m / 27'11"	9.24m / 30'4"
X	1.35m / 4'7"	1.35m / 4'7"
Y	1.00m / 3'4"	1.00m / 3'4"

