

# Turbo Mower Offset



The Turbo Mower Offset range offers operators a choice of cutting widths at cost effective prices.

A well designed and constructed range, the Turbo Mower Offset is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

## Key Features

- 1.6m, 2.2m and 2.5m cutting widths
- Three point linkage mounting
- PTO overrun protection, safety breakaway and double-skin protection
- 155 degrees of head movement
- Vertical and horizontal hydraulic adjustment
- Fuel-efficient, high-performance double spiral rotor
- Cutting height of 30mm - 80mm
- Maximum cutting diameter of 50mm



## Product Specification

● Standard ○ Optional — Not Available

Turbo Mower Offset	160	220	220HD	250HD
Working Width	1.6m / 5'3"	2.2m / 7'2"	2.2m / 7'2"	2.5m / 8'2"
Weight	610kg / 1345lbs	705kg / 1554lbs	1060kg / 2310lbs	1210kg / 2668lbs
Front Protection	Steel Flap	Steel Flap	Steel Flap	Steel Flap
Rear Protection	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap
Linkage	Cat 11	Cat 11	Cat 11 / 111	Cat 11 / 111
PTO Speed (rpm)	540	540	540	540
No of Belts	3	3	4	5
Front Mount	—	—	—	—
No of Flails (Whale Tail)	16	22	22	24
Width of Flails	110mm / 4 <sup>5</sup> / <sub>16</sub> "	110mm / 4 <sup>5</sup> / <sub>16</sub> "	110mm / 4 <sup>5</sup> / <sub>16</sub> "	135mm / 5 <sup>5</sup> / <sub>16</sub> "
Power Requirements (min)	50hp	60hp	90hp	95hp
Cutting Height	30-80mm 1 <sup>3</sup> / <sub>16</sub> " - 3 <sup>1</sup> / <sub>16</sub> "	30-80mm 1 <sup>3</sup> / <sub>16</sub> " - 3 <sup>1</sup> / <sub>16</sub> "	40mm 1 <sup>9</sup> / <sub>16</sub> "	40mm 1 <sup>9</sup> / <sub>16</sub> "
Roller Size	140mm / 5 <sup>1</sup> / <sub>2</sub> "	140mm / 5 <sup>1</sup> / <sub>2</sub> "	170mm / 6 <sup>11</sup> / <sub>16</sub> "	170mm / 6 <sup>11</sup> / <sub>16</sub> "



**Want to know more about the Turbo Mower Offset range?**

Scan the QR code with a smart phone or tablet to instantly view the page.