

Wren

Compact yet powerful, the Wren is the latest addition to the range of arm mowers from Bomford Turner and offers an excellent entry-level solution to your landscaping maintenance needs.

Fitted with twin pumps and fully independent hydraulics, the Wren can operate a range of different attachments.

Key Features

- 3.5m reach
- Left or right hand cutting option
- Cable control
- Mechanical breakout
- Cutter bar option



Want to know more about the Wren range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: www.bomford-turner.com/landscape/arm-mowers/wren/





Cable rotor reverse

Fitted as standard. Ideal for cutting both brush and grass.



Fully independent hydraulics

For continuous use. Twin pumps with separate oil tank.



Multi-purpose flails

For grass and hedges.

Product Specification

● Standard ○ Optional — Not Available

Wren	3.5m (11'5")
Tractor requirements	
Minimum horse power	25hp
Minimum weight	750kg / 1653lbs
Base unit mounting options	
Front mount	—
Mid-mount	—
Rear mount	●
Three point linkage (Cat 1 & Cat 11)	●
Axle bracket	—
Overall machine parameters	
Machine weight with head and oil	350kg / 772lbs
Capacity of oil tank	55L / 14.5USG
Controls	
Cable Control (CC)	●
Electronic proportional control (EPP)	—
Intelligent control system (ICS)	—
Low pressure hydraulics (LPH)	—
Cable rotor reverse	●
Electronic rotor reverse	—
Hydraulic System	
System capability	30hp
Pump flow rate (min)	50L / 13.2USG
Pump type (Gear / Piston / Helical)	Gear
Pump arrangement (Twin / Tandem Inline)	Twin
Independent hydraulics	●
Oil cooler	○

Wren	3.5m (11'5")
Arm features and main frame	
Telescopic arm	—
Telescopic arm stroke	—
Power slew	—
Power slew angle	—
Gravity breakout	●
Hydraulic breakout	—
Armfloat - manual	●
Armfloat - electronic	—
Headfloat - manual	●
Headfloat - electronic	—
Left hand cutting	●
Right hand cutting	●
Left and right hand cutting	—
Cutting heads	
0.8m Flailhead	●
1.5m Cutter Bar	○



Gravity breakout system

For protecting drive and machine during operation.

Working Reach

Head used for calcs: **0.8m Flail Head**

	Wren 3.5m (11'5")
A	3.3m / 10'10"
B	3.3m / 10'10"
C	2.2m / 7'3"
D	1.8m / 5'11"
E	3.5m / 11'6"
X	1.0m / 3'3"
Y	0.7m / 2'4"

