

Hawk Evo Power Plus

The Hawk Evo Power Plus is perfect for contractors and municipal environments.

These features include integral road lighting, tubular 3 point linkage and power slew with hydraulic breakout.

Key Features

- 6.5m and 7.0m reach options
- Parallel arm standard
- Steel hose covers
- Choice of flails, heads and cutter bars
- Power slew
- Oil cooler standard



Want to know more about the Hawk Evo Power Plus range?

Scan the QR code with a smart phone or tablet to instantly view the page.





Steel hose covers

Adding additional protection to drive motor hoses.



Parallel arm geometry

Available as standard.



Road lights

Fitted as standard.

Product Specification

● Standard ○ Optional — Not Available

Hawk Evo Power Plus	6.5m P (21'4")	7.0m P (23')
Tractor requirements		
Minimum horse power	100hp	100hp
Minimum weight	5500kg 12125lbs	5500kg 12125lbs
Base unit mounting options		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (Cat 11)	●	●
Axle bracket	○	○
Overall machine parameters		
Machine weight with head and oil	1740kg 3836lbs	1780kg 3924lbs
Capacity of oil tank	200L 52.8USG	200L 52.8USG
Weight of machine with oil but without head	1500kg 3307lbs	1540kg 3395lbs
Controls		
Cable Control (CC)	—	—
Low pressure hydraulics (LPH)	—	—
Electronic proportional control (EPP)	—	—
Intelligent control system (ICS)	●	●
Cable rotor reverse	○	○
Electronic rotor reverse	○	○
Hydraulic System		
System capability	74hp	74hp
Pump flow rate	125L 33USG	125L 33USG
Pump type (Gear / Piston / Helical)	Gear	Gear
Pump arrangement (Twin / Tandem Inline)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	○	○

Hawk Evo Power Plus	6.5m P (21'4")	7.0m P (23')
Arm features and main frame		
Telescopic arm	●	●
Telescopic arm stroke	900mm 3'	900mm 3'
Power slew	●	●
Power slew angle	94°	94°
Gravity breakout protection	—	—
Hydraulic breakout protection	●	●
Arm float - manual operation	○	○
Arm float - electronic operation	○	○
Head float - manual operation	○	○
Head float - electronic operation	●	●
Left hand cutting	○	○
Right hand cutting	○	○
Left and right hand cutting	—	—
Arm attachments available		
Variable track bracket (VTB)	—	—
Sheartrim cutter bar	○	○
Pro-Saw	○	○
Ditch cleaner	○	○
Rotary head	○	○
Accessories		
Road lights	●	●
Debris blower	○	○
Cab guard kit	●	●
Cutting heads (For Flail compatibility see page 97)		
1.2m Pro-Trim with 115/150mm roller	●	●
1.2m Pro-Trim ISMP with 115/150mm roller	○	○
1.5m Pro-Trim with 115/150mm roller	○	○



Oil cooler as standard

High level keeping clear of any cutting debris.

Working Reach

Head used for calcs: 1.2 Pro-Trim

	Hawk Evo 6.5m P (21'4")	Hawk Evo 7.0m P (23')
A	6.47m / 21'3"	7.03m / 23'1"
B	6.21m / 20'11"	6.91m / 22'8"
C	4.68m / 15'4"	4.83m / 15'10"
D	4.97m / 16'4"	5.69m / 18'8"
E	6.62m / 21'9"	7.40m / 24'3"
X	1.35m / 4'5"	1.35m / 4'5"
Y	1.0m / 3'4"	1.0m / 3'4"

