

Buccaneer

Suitable for use with tractors of between 110hp to 120hp and features a heavy duty gearbox. The robust build means that the smaller SD machine weighs 1,260kg while the wider HDX model comes in at 2,150kg.

The standard specification of the new Bomford Buccaneer HDX includes a front double-row chain guard, Cat 11/111 three-point linkage and heavy-duty replaceable skids. A front mounted version of the Buccaneer HDX is also available.

Key Features

- Fixed or swinging flail options
- 5 belt driven (8 on HDX model)
- 110-120hp tractor requirement options
- Rear pushbar standard on both models
- Replaceable skids
- 540rpm or 1,000rpm



Want to know more about the Buccaneer range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard ○ Optional — Not Available

Buccaneer	SD 220	HDX 220	HDX 250
Working Width	2.2m / 7'2"	2.2m / 7'2"	2.5m / 8'2"
Overall Width	2.5m / 8'2"	2.76m / 9'	3.05m / 10'
Weight	1260kg / 2778lbs	2250kg / 4960lbs	2650kg / 5842lbs
Front Protection	Chains	Chains	Chains
Rear Protection	Hydraulic Opening Hood	Hydraulic Opening Hood	Hydraulic Opening Hood
Rear Protection	Mechanical Push Bar	Hydraulic Push Bar	Hydraulic Push Bar
Linkage	Cat 11 / 111	Cat 11 / 111	Cat 11 / 111
PTO Speed (rpm)	540	1000	1000
No of Belts	5	8	8
Front Mount	○	○	—
Flail Type	Swinging Hammer	Fixed Hammer	Fixed Hammer
No of Flails (Whale Tail)	40	54	60
Opening Rear Hood	●	●	●
Power Requirements (min)	110hp	120hp	130hp
Cutting Diameter	100mm / 3 ¹⁵ / ₁₆ "	200mm / 8"	200mm / 8"

Heavy duty drive

5 belt drive on SD models and 8 belts (dual drive) on HDX ranges.

Swinging hammer options

Ideal for use on green vegetation for shredding.



Fixed hammers

Options available. Suitable for managing wooded areas and providing a chipped wood finish. Benefits are mulching the debris within the soil leaving the ground level.

Push bars

Rear push bars fitted as standard enable material to be pushed over and presented to the cutting rotor. Hydraulic rear hood for closing down rear opening for mulching.

Protection

Double rows of heavy chains and adjustable skids.

