

Flailbot Compact Stage V / T4 Final

Flailbot Compact Stage V / T4 Final carries all the same features as the Mini model, with the bigger Flailbot 50hp Perkins industrial powerplant.

The compact size, but powerful 50hp Perkins engine makes the compact model a contractors first choice. With the added feature of manual wind out track width as standard, and a number of attachments available.

Key Features

- Perkins 50hp industrial engine
- 1300mm (51") cutting head
- Manually wind out track frame
- Auto hydraulic track tension system
- Full engine covers as standard



**Want to know more about the
Flailbot Compact Stage V / T4 Final**

Scan the QR code with a smart phone or tablet to instantly view the page.





Radiator cooler cover

Hinged cooler guard for easy access.



Easy access

Engine protection covers easily removed for fast and simple access for maintenance.

Flailbot Compact Stage V / T4 Final Weights & Dimensions


Engine Size / Capacity
50hp /
 1.6 Litres / 101.4 in³

Flailbot with Oil & Fuel
1110 kg / 2,425lbs
 1300 Flail Head
210 kg / 462 lbs

Features & Specification

Flailbot	Compact Stage V / T4 Final (50hp)
Operation	
Max Slope	55°
Transmission	Hydrostatic
Speed	0-7 km/h
Weight	1110kg / 2,425lbs
Engine	
Brand / Make	Perkins
Model	3 Cylinders, Diesel
Engine Size	1.662 Litres / 101.4 in ³
Power	36 kW / 49 Cv
Max Torque	166 Nm / 122 ft-lb @ 1800 rpm
Intake	Turbocharged
Cooling	Liquid
Air Filter	Dry
Diesel Tank Capacity	24 Litres / 6.3 USG
Engine Oil Quantity	6 Litres / 2 USG
Electrical Circuit	
Operating Voltage	12 Vcc
Alternator	85 Amp
Battery	44 Ah

Flailbot	Compact Stage V / T4 Final (50hp)
Hydraulic System	
Displacement	Tandem piston pump with variable engine size and closed circuit
Displacement Capacity	104 Litres max @ 2750 rpm 27 USG max @ 2750 rpm
Displacement Pressure	320 Bar max
Services	Gear Pump
Services Capacity	15 Litres max @ 2750 rpm 4 USG max @ 2750 rpm
Services Pressure	200 Bar max
Tool	Closed Circuit Piston Pump
Tool Capacity	77 Litres max @ 2750 rpm 20 USG max @ 2750 rpm
Tool Pressure	320 Bar max
Oil Tank Capacity	25 Litres / 7 USG
Operating Oil Quantity	35 Litres / 9 USG
Controls	
Brand	Scanreco
Frequency	2.4 Ghz
Range Signal	150m / 492'
Battery	Rechargeable



Working range

All Flailbot models have an impressive working range of 150m (492').

