

# Hawk Evo

The Hawk Evo is perfect for farmers, contractors and municipal environments.

Fitted with a powerful 104 litre drive system, and options to upgrade to 125 litre, the Hawk Evo offers a machine for every application.

## Key Features

- 5.4m or 6.0m reach
- 1.2m or 1.5m Pro-Trim head option
- 104 l/min independent hydraulic system
- 94° of slew (max non parallel systems)



Want to know more about the Hawk Evo range?

Scan the QR code with a smart phone or tablet to instantly view the page.



## Product Specification

● Standard ○ Optional — Not Available

Hawk Evo	5.4m P (17'9")	6.0m P (19'8")
<b>Tractor requirements</b>		
Minimum horse power	65hp	65hp
Minimum weight	4500kg / 9921lbs	5000kg / 11023lbs
<b>Base unit mounting options</b>		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (Cat 11)	●	●
Axle bracket	○	○
<b>Overall machine parameters</b>		
Machine weight with head and oil	1340kg / 2954lbs	1490kg / 3285lbs
Capacity of oil tank	180L / 47.6USG	180L / 47.6USG
Weight of machine with oil but without head	1100kg / 2425lbs	1250kg / 2756lbs
<b>Controls</b>		
Cable Control (CC)	●	●
Low pressure hydraulics (LPH)	○	○
Electronic proportional control (EPP)	○	○
Intelligent control system (ICS)	○	○
Cable rotor reverse	○	○
Electronic rotor reverse	○	○
<b>Hydraulic System</b>		
System capability	60hp	60hp
Pump flow rate	104L / 27.5USG	104L / 27.5USG
Pump type (Gear / Piston / Helical)	Gear	Gear
Pump arrangement (Twin / Tandem / InLine)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	○	○

Hawk Evo	5.4m P (17'9")	6.0m P (19'8")
<b>Arm features and main frame</b>		
Telescopic arm	—	—
Telescopic arm stroke	—	—
Power slew	●	●
Power slew angle	94°	94°
Gravity breakout protection	—	—
Hydraulic breakout protection	●	●
Arm float - manual operation	○	○
Arm float - electronic operation	○	○
Head float - manual operation	●	●
Head float - electronic operation	○	○
Left hand cutting	○	○
Right hand cutting	○	○
Left and right hand cutting	—	—
<b>Arm attachments available</b>		
Variable track bracket (VTB)	—	—
Sheartrim cutter bar	○	○
Pro-Saw	○	○
Ditch cleaner	○	○
Rotary head	—	—
<b>Accessories</b>		
Road lights	●	●
Debris blower	○	○
Cab guard kit	●	●
<b>Cutting heads</b> (For Flail compatibility see page 89)		
1.2m Pro-Trim with 115/150mm roller	●	●
1.2m Pro-Trim ISMP with 115/150mm roller	○	○
1.5m Pro-Trim with 115/150mm roller	○	○

**Fully enclosed hydraulics**  
Keeping components protected.

**Oil cooler**  
Standard on all models  
(cable controls as an option).

**Road lights**  
Fitted as standard.



**Slimline compact transport position**

Keeping weight closer to tractor for faster road speeds.

## Working Reach

Head used for calcs: 1.2 Pro-Trim

	Hawk Evo 5.4m P (17'9")	Hawk Evo 6.0m P (19'8")
<b>A</b>	5.35m / 17'7"	5.95m / 19'6"
<b>B</b>	5.39m / 17'8"	6.11m / 20'1"
<b>C</b>	3.64m / 11'11"	4.32m / 14'2"
<b>D</b>	4.25m / 13'11"	4.74m / 15'7"
<b>E</b>	5.89m / 19'4"	6.39m / 21'
<b>X</b>	1.35m / 4'5"	1.35m / 4'5"
<b>Y</b>	1.0m / 3'3"	1.0m / 3'3"

