

# Hawk Evo Power Plus

The Hawk Evo Power Plus is perfect for contractors and municipal environments.

These features include integral road lighting, tubular 3 point linkage and power slew with hydraulic breakout.

## Key Features

- 6.5m and 7.0m reach options
- Parallel arm standard
- Steel hose covers
- Choice of flails, heads and cutter bars
- Power slew
- Oil cooler standard



**Want to know more about the Hawk Evo Power Plus range?**

Scan the QR code with a smart phone or tablet to instantly view the page.





## Product Specification

● Standard ○ Optional — Not Available

Hawk Evo Power Plus	6.5m P (21'4")	7.0m P (23')
<b>Tractor requirements</b>		
Minimum horse power	100hp	100hp
Minimum weight	5500kg 12125lbs	5500kg 12125lbs
<b>Base unit mounting options</b>		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (Cat 11)	●	●
Axle bracket	○	○
<b>Overall machine parameters</b>		
Machine weight with head and oil	1740kg 3836lbs	1780kg 3924lbs
Capacity of oil tank	200L 52.8USG	200L 52.8USG
Weight of machine with oil but without head	1500kg 3307lbs	1540kg 3395lbs
<b>Controls</b>		
Cable Control (CC)	○	○
Low pressure hydraulics (LPH)	○	○
Electronic proportional control (EPP)	○	○
Intelligent control system (ICS)	●	●
Cable rotor reverse	○	○
Electronic rotor reverse	○	○
<b>Hydraulic System</b>		
System capability	74hp	74hp
Pump flow rate	125L 33USG	125L 33USG
Pump type (Gear / Piston / Helical)	Gear	Gear
Pump arrangement (Twin / Tandem / Inline)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	○	○

Hawk Evo Power Plus	6.5m P (21'4")	7.0m P (23')
<b>Arm features and main frame</b>		
Telescopic arm	●	●
Telescopic arm stroke	900mm 3'	900mm 3'
Power slew	●	●
Power slew angle	94°	94°
Gravity breakout protection	—	—
Hydraulic breakout protection	●	●
Arm float - manual operation	○	○
Arm float - electronic operation	○	○
Head float - manual operation	○	○
Head float - electronic operation	●	●
Left hand cutting	○	○
Right hand cutting	○	○
Left and right hand cutting	—	—
<b>Arm attachments available</b>		
Variable track bracket (VTB)	—	—
Sheartrim cutter bar	○	○
Pro-Saw	○	○
Ditch cleaner	○	○
Rotary head	○	○
<b>Accessories</b>		
Road lights	●	●
Debris blower	○	○
Cab guard kit	●	●
<b>Cutting heads (For Flail compatibility see page 89)</b>		
1.2m Pro-Trim with 115/150mm roller	●	●
1.2m Pro-Trim ISMP with 115/150mm roller	○	○
1.5m Pro-Trim with 115/150mm roller	○	○

### Steel hose covers

Adding additional protection to drive motor houses.

### Parallel arm geometry

Available as standard.


### Oil cooler as standard

High level keeping clear of any cutting debris.

## Working Reach

Head used for calcs: 1.2 Pro-Trim

	Hawk Evo 6.5m P (21'4")	Hawk Evo 7.0m P (23')
<b>A</b>	6.47m / 21'3"	7.03m / 23'1"
<b>B</b>	6.21m / 20'11"	6.91m / 22'8"
<b>C</b>	4.68m / 15'4"	4.83m / 15'10"
<b>D</b>	4.97m / 16'4"	5.69m / 18'8"
<b>E</b>	6.62m / 21'9"	7.40m / 24'3"
<b>X</b>	1.35m / 4'5"	1.35m / 4'5"
<b>Y</b>	1.0m / 3'3"	1.0m / 3'3"



### Road lights

Fitted as standard.