

Turbo Mower

The Turbo Mower Elite, Euro and Turbo Pro range offers operators a huge choice of cutting widths at very cost effective prices.

A well designed and constructed range, the Turbo Mower is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

Key Features

- Choice of cutting widths available
- Front mount options
- Hydraulic offset standard on all models
- Standard fitted roller and side skids
- Cat 11 three point linkage mounted
- Over run clutch protected



Want to know more about the Turbo Mower range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard ○ Optional — Not Available

Turbo Mower	ELITE 130 COMPACT	ELITE 150 COMPACT	ELITE 180 COMPACT	ELITE 200	ELITE 220	ELITE 250	ELITE 280
Working Width	1.3m / 4'3"	1.5m / 4'9"	1.8m / 5'9"	2.0m / 6'6"	2.2m / 7'2"	2.5m / 8'2"	2.8m / 9'2"
Overall Width	1.45m / 4'9"	1.65m / 5'5"	1.985m / 6'5"	2.2m / 7'2"	2.4m / 13'1"	2.7m / 8'9"	3.02m / 9'9"
Weight	250kg / 551lbs	290kg / 639lbs	390kg / 860lbs	690kgs / 1521lbs	730kg / 1609lbs	815kg / 1797lbs	1080kg / 2381lbs
Hydraulic Offset	○	○	●	●	●	●	●
Hydraulic Offset	400mm / 5 3/4"	400mm / 5 3/4"	400mm / 5 3/4"	400mm / 5 3/4"	400mm / 5 3/4"	400mm / 5 3/4"	400mm / 5 3/4"
Front Protection	Steel Flap	Steel Flap	Steel Flap	Steel Flap	Steel Flap	Steel Flap	Chains
Rear Protection	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap
Linkage	Cat 1	Cat 1	Cat 1 / 11	Cat 11	Cat 11	Cat 11	Cat 11
PTO speed (rpm)	540	540	540	540	540	540	1000
Number of Belts	2	2	3	4	4	4	5
Mulching Bars	—	—	●	●	●	●	●
Front mount	—	—	—	—	—	—	—
No. of Flails (Whale Tail)	15	18	24	22	22	24	29
Width of Flails (Whale Tail)	80mm / 3 1/4"	80mm / 3 1/4"	85mm / 3 1/4"	135mm / 5 3/16"	135mm / 5 3/16"	135mm / 5 3/16"	135mm / 5 3/16"
Opening Rear Hood	—	—	●	●	●	●	—
Power requirements (min)	25 hp	25 hp	45-60 hp	55-75 hp	65-90 hp	75-100 hp	85-110 hp
Cutting height	32-111mm 1 1/4" - 4 3/8"	32-111mm 1 1/4" - 4 3/8"	30-60mm 1 3/16" - 2 3/8"	30-60mm 1 3/16" - 2 3/8"	30-60mm 1 3/16" - 2 3/8"	30-60mm 1 3/16" - 2 3/8"	30-60mm 1 3/16" - 2 3/8"
Roller size	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	170mm / 6 11/16"	170mm / 6 11/16"	170mm / 6 11/16"	220mm / 8 11/16"



Wear skirts

Simple greasing and replaceable skirts.



Hydraulic side shift

Hydraulic offset function on all models.



Easy adjustment

Simple belt tensing system with oil filled drive tube.

Turbo Mower	EURO 250	EURO 280	TURBO PRO 280	TURBO PRO 300
Working Width	2.5m / 8'2"	2.8m / 9'2"	2.8m / 9'2"	3.0m / 9'9"
Overall Width	2.7m / 8'9"	3.05m / 10'	3.05m / 10'	3.2m / 10'5"
Weight	1140kg / 2513lbs	1160kg / 2557lbs	1330kg / 2932lbs	1430kg / 3153lbs
Hydraulic Offset	●	●	●	●
Hydraulic Offset	500mm / 19 11/16"	500mm / 19 11/16"	500mm / 19 11/16"	500mm / 19 11/16"
Front Protection	Steel Flap	Steel Flap	Chains	Chains
Rear Protection	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap
Linkage	Cat 11	Cat 11	Cat 11 / 111	Cat 11 / 111
PTO speed (rpm)	1000	1000	1000	1000
Number of Belts	6	6	6	6
Mulching Bars	●	●	●	●
Front mount	●	●	●	●
No. of Flails (Whale Tail)	32	32	32	34
Width of Flails (Whale Tail)	100mm / 3 15/16"	100mm / 3 15/16"	100mm / 3 15/16"	100mm / 3 15/16"
Opening Rear Hood	—	—	●	●
Power requirements (min)	45-60 hp	55-75 hp	65-90 hp	75-100 hp
Cutting height	45mm 1 3/4"	45mm 1 3/4"	45mm 1 3/4"	45mm 1 3/4"
Roller size	170mm / 6 11/16"	170mm / 6 11/16"	220mm / 8 11/16"	220mm / 8 11/16"



Flail type

Heavy duty whale tail type flail fitted as standard.