

# Twin-Blade

The new, more robust Twin-Blade is a flexible, efficient, in-line topper or fully offset - perfect for paddocks and headlands.

The range extends from 1.25m and semi-offset to 2.8m. The Twin-Blade also features cast-iron gearboxes and protected drivelines. Simple, adjustable skids on this machine are key to a smooth operation.

## Key Features

- Shaft driven
- 1.25m, 1.45m, 1.85m, 2.4m and 2.8m cutting width
- Variable cutting height
- Shearbolt and overrun gear box protection
- Cat 1 or Cat 11 three point linkage
- A-Frame mounting option



**Want to know more about the Twin Blade range?**

Scan the QR code with a smart phone or tablet to instantly view the page.





## Product Specification

Twin-Blade	TB125	TB145	TB185	TB240	TB280
Cutting Width	1210mm / 4'	1420mm / 4'8"	1725mm / 5'11"	2600mm / 8'6"	2800mm / 9'2"
Overall Width (Transport)	1345mm / 4'5"	1545mm / 5'1"	1875mm / 7'6"	2850mm / 9'4"	3050mm / 10'
Weight	220kg / 485lbs	265kg / 584lbs	310kg / 683lbs	410kg / 904lbs	450kg / 992lbs
Linkage Mounting	Cat 1	Cat 1	Cat 11	Cat 11	Cat 11
PTO Speed (rpm)	540	540	540	540	540
Number of Rotors	1	1	1	2	2
Number of Blades	2	2	3	4	4
Power Requirement (min)	25hp	25hp	45hp	50hp	60hp
PTO shaft protection	Shearbolt	Shearbolt	Slip clutch	Slip clutch	Slip clutch
Cutting Height	10-90mm 3/8" - 3 3/16"	10-90mm 3/8" - 3 3/16"	10-90mm 3/8" - 3 3/16"	30-90mm 1 1/16" - 3 3/16"	30-90mm 1 1/16" - 3 3/16"
Semi Offset	Inline	Inline	Inline	Inline	Inline

### Blade carrier

Fitted with updraft blades.

### Floating headstock

Standard on all models.

### Adjustable skids

Simple to adjust for smooth operation.



**Inline 1.45m 4'8"**  
Ideal for paddock topping.