

Twin-Blade HD

The Twin-Blade HD is a rugged topper available in 8' or 9' cutting widths. The HD has the standard features of both adjustable depth skids, and the adjustable castor wheels to control cutting height.

The HD model is constructed with a 4mm Domex steel and a main input gearbox capable of 150HP, and fitted as standard with a durable slip clutch PTO shaft. There are a number of blade options available, from standard grass blades, dome anti scalp kit, and shredder blades.

Key Features

- Shaft driven
- 2.4m and 2.7m cutting width
- Adjustable depth skids and adjustable castor wheels
- Variable cutting height
- 4mm Domex steel construction
- Various blade options available
- Cat 11 three point linkage



Product Specification

Twin-Blade HD	2400	2700
Cutting Width	2.4m / 7'10"	2.7m / 8'10"
Transport Width	2.69m / 8'10"	2.98m / 9'9"
Power Requirements	80hp	110hp
Length	2.95m / 9'8"	2.95m / 9'8"
Cutting Height	50mm-175mm / 2"-7"	50mm-175mm / 2"-7"
PTO Speed	1000rpm	1000rpm
Number of Rotors	2	2
Number of Blade Carriers	2	2
Number of Blades	4	4
Number of Skids	2	2
Weight	856kg / 1887lbs	923kg / 2034lbs



Want to know more about the Twin Blade HD range?

Scan the QR code with a smart phone or tablet to instantly view the page.