

Turbo Mower Offset



The Turbo Mower Offset range offers operators a choice of cutting widths at cost effective prices.

A well designed and constructed range, the Turbo Mower Offset is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

Key Features

- 1.6m, 2.2m and 2.5m cutting widths
- Three point linkage mounting
- Left or right hand cutting options available
- PTO overrun protection, safety breakaway and double-skin protection
- 132 degrees of head movement
- Vertical and horizontal hydraulic adjustment
- Fuel-efficient, high-performance double spiral rotor
- Cutting height of 30mm - 80mm
- Maximum cutting diameter of 50mm



Want to know more about the Turbo Mower Offset range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard
 ○ Optional
 — Not Available

Turbo Mower Offset	160	220	220HD	250HD
Working Width	1.6m / 5'3"	2.2m / 7'2"	2.2m / 7'2"	2.5m / 8'2"
Weight	610kg / 1345lbs	710kg / 1565lbs	1060kg / 2310lbs	1260kg / 2779lbs
Front Protection	Steel Flap	Steel Flap	Steel Flap	Steel Flap
Rear Protection	Rubber Flap	Rubber Flap	Rubber Flap	Rubber Flap
Linkage	Cat 11	Cat 11	Cat 11 / 111	Cat 11 / 111
PTO Speed (rpm)	540	540	540	540
No of Belts	3	3	4	5
Front Mount	—	—	—	—
No of Flails (Whale Tail)	16	22	22	24
Width of Flails	110mm / 4 ³ / ₁₆	110mm / 4 ³ / ₁₆	110mm / 4 ³ / ₁₆	135mm / 5 ³ / ₁₆
Power Requirements (min)	50hp	60hp	90hp	95hp
Cutting Height	30-80mm 1 ¹ / ₁₆ " - 3 ¹ / ₈ "	30-80mm 1 ¹ / ₁₆ " - 3 ¹ / ₈ "	30-80mm 1 ¹ / ₁₆ " - 3 ¹ / ₈ "	30-80mm 1 ¹ / ₁₆ " - 3 ¹ / ₈ "
Roller Size	140mm / 5 ¹ / ₂ "	140mm / 5 ¹ / ₂ "	170mm / 6 ¹ / ₁₆ "	170mm / 6 ¹ / ₁₆ "

Guarding

Leading edge debris rail and rear rubber flaps.

Parallel linkage

Standard on all models.

Replacable skids

Simple to replace.

Transport position

Transports within tractor width.

