

Buzzard Evo

The Buzzard Evo range has been specifically designed for the large scale contractor and agency.

With a large choice in specification, and fully proportional controls.

Key Features

- 7.25m or 8m reach
- 1.2m or 1.5m cutting heads
- Oil cooled as standard
- ICS fully proportional controls
- 137L (85hp) gear upgrade system option



Want to know more about the Buzzard Evo range?

Scan the QR code with a smart phone or tablet to instantly view the page.

Product Specification

● Standard ○ Optional — Not Available

Buzzard Evo	7.25m T (23'9")	8.0m T (26'3")
Tractor requirements		
Minimum horse power	120hp	140hp
Minimum weight	5500kg 12125lbs	6000kg 13228lbs
Base unit mounting options		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (Cat 11)	—	—
Axle bracket	●	●
Overall machine parameters		
Machine weight with head and oil	2300kg 5070lbs	2570kg 5666lbs
Capacity of oil tank	250L 66USG	250L 66USG
Weight of machine with oil but without head	2020kg 4453lbs	2290kg 5049lbs
Controls		
Cable Control (CC)	—	—
Low pressure hydraulics (LPH)	—	—
Electronic proportional control (EPP)	—	—
Intelligent control system (ICS)	●	●
Cable rotor reverse	○	○
Electronic rotor reverse	●	●
Hydraulic system		
System capability	74hp	74hp
Pump flow rate	125L 33USG	125L 33USG
Pump type (Gear/Piston/Helical)	Gear	Gear
Pump arrangement (Twin/In-line)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	●	●

Buzzard Evo	7.25m T (23'9")	8.0m T (26'3")
Arm features and main frame		
Forward arm	—	—
Telescopic arm	●	●
Telescopic arm stroke	1300mm 4'3"	1450mm 4'9"
Power slew	●	●
Power slew angle	94°	94°
Gravity breakout protection	—	—
Hydraulic breakout protection	●	●
Arm float - manual operation	—	—
Arm float - electronic operation	●	●
Head float - manual operation	○	○
Head float - electronic operation	●	●
Left hand cutting	○	○
Right hand cutting	○	○
Left and right hand cutting	—	—
Arm attachments available		
Variable track bracket (VTB)	○	○
Sheartrim cutter bar	○	○
Pro-Saw	○	○
Ditch cleaner	○	○
Rotary head	○	○
Accessories		
Road Lights	●	●
Debris Blower	○	○
Cab Guard Kit	●	●
Cutting heads (For Flail compatibility see page 79)		
1.2m Pro-Cut - 115/150mm roller	●	●
1.5m Pro-Cut - 115/150mm roller	○	○
1.2m Pro-Cut ISMP - 115/150mm roller	○	○
2m HD head	○	○

Telescopic arm

Gives increased flexibility.

Powerful 74hp hydraulics

For continuous use. Twin pumps with separate oil tank.

Oil cooler

Standard on all models
(cable controls as an option).

Fully enclosed hydraulics

Keeping components protected from the elements.

Working Reach

Head used for calcs: 1.2 Pro-Cut

	Buzzard Evo 7.25m T (23'9")	Buzzard Evo 8.0m T (26'3")
A	7.3m / 23'11"	7.94m / 26'1"
B	7.64m / 25'1"	8.07m / 26'6"
C	5.25m / 17'7"	5.91m / 19'5"
D	6.25m / 20'6"	6.86m / 22'6"
E	8.71m / 28'7"	8.87m / 29'1"
X	1.35m / 4'7"	1.35m / 4'7"
Y	1.0m / 3'3"	1.0m / 3'3"

