Flailbot Compact Stage V / T4 Final

Flailbot Compact Stage V / T4 Final carries all the same features as the Mini model, with the bigger Flailbot 50hp Perkins industrial power plant.

The compact size, but powerful 50hp Perkins engine makes the compact model a contractors first choice. With the added feature of manual wind out track width as standard, and a number of attachments available.

BOMFORD

Key Features

- Perkins 50hp industrial engine
- 1300mm (51″) cutting head
- Manually wind out track frame
- Auto hydraulic track tension system
- Full engine covers as standard



Want to know more about the Flailbot Compact Stage V / T4 Final Scan the QR code with a smart phone or

Scan the QR code with a smart phor tablet to instantly view the page.



Radiator cooler cover Hinged cooler guard for easy access.



Easy access Engine protection covers easily removed for fast and simple access for maintenance.

Flailbot Compact Stage V / T4 Final Weights & Dimensions

Engine Size / Capacity 50hp /

1.6 Litres / 101.4 in³ Flailbot with Oil & Fuel

1110 kg / 2,425lbs

1300 Flail Head **210 kg /** 462 lbs


Features & Specification


Flailbot	Compact Stage V / T4 Final (50hp)
Operation	
Max Slope	55°
Transmission	Hydrostatic
Speed	0-7 km/h
Weight	1110kg / 2,425lbs
Engine	
Brand / Make	Perkins
Model	3 Cylinders, Diesel
Engine Size	1.662 Litres / 101.4 in ³
Power	36 kW / 49 Cv
Max Torque	166 Nm / 122 ft-lb @ 1800 rpm
Intake	Turbocharged
Cooling	Liquid
Air Filter	Dry
Diesel Tank Capacity	24 Litres / 6.3 USG
Engine Oil Quantity	6 Litres / 2 USG
Electrical Circuit	
Operating Voltage	12 Vcc
Alternator	85 Amp
Battery	44 Ah

Hydraulic SystemIndem piston pump with variable engine size and closed circuitDisplacementTandem piston pump with variable engine size and closed circuitDisplacement Capacity104 Litres max @ 2750 rpm 27 USG max @ 2750 rpm 27 USG max @ 2750 rpm 27 USG max @ 2750 rpm 4 USG max @ 2750 rpm 4 USG max @ 2750 rpmServicesGear PumpServices Capacity15 Litres max @ 2750 rpm 4 USG max @ 2750 rpmServices Pressure200BarmaxToolClosed Circuit Piston PumpTool Capacity320 Bar maxOiol Capacity320 Bar maxOiol Tank Capacity32 Litres / 7 USGOperating Oil Quantity35 Litres / 9 USGPandScanrecoFrequency2.4 GhzRange Signal150m / 492'BatteryRechargeable	Flailbot	Compact Stage V / T4 Final (50hp)
engine size and closed circuitDisplacement Capacity104 Litres max @ 2750 rpm 27 USG max @ 2750 rpm 27 USG max @ 2750 rpmDisplacement Pressure320 Bar maxServices Capacity15 Litres max @ 2750 rpm 4 USG max @ 2750 rpmServices Pressure200Bar maxToolClosed Circuit Piston PumpTool Capacity77 Litres max @ 2750 rpm 	Hydraulic System	
27 USG max @ 2750 rpmDisplacement Pressure320 Bar maxServicesGear PumpServices Capacity15 Litres max @ 2750 rpmServices Pressure200Bar maxToolClosed Circuit Piston PumpTool Capacity77 Litres max @ 2750 rpmDool Pressure320 Bar maxOil Tank Capacity320 Lisres / 10SGOperating Oil Quantity35 Litres / 10SGBrandScanrecoFrequency2.4 GhzRange Signal150m / 492'	Displacement	
ServicesGear PumpServices Capacity15 Litres max @ 2750 rpm 4 USG max @ 2750 rpm 4 USG max @ 2750 rpmServices Pressure200BarmaxToolClosed Circuit Piston PumpTool Capacity77 Litres max @ 2750 rpm 20 USG max @ 2750 rpmTool Pressure320 Bar maxOil Tank Capacity25 Litres / 1 USGOperating Oil Quantity35 Litres / 9 USGBrandScanrecoFrequency2.4 GhzRange Signal150m / 492'	Displacement Capacity	· · · ·
Services Capacity15 Litres max@ 2750 rpm 4 USG max@ 2750 rpmServices Pressure200BarmaxToolClosed Circuit Piston PumpTool Capacity77 Litres max@ 2750 rpm 20 USG max@ 2750 rpmTool Pressure320 Bar maxOil Tank Capacity25 Litres / 7 USGOil Tank Capacity35 Litres / 9 USGControlsBrandScanrecoFrequency2.4 GhzRange Signal150m / 492'	Displacement Pressure	320 Bar max
Services Capacity4 USG max @ 2750 rpmServices Pressure200BarmaxToolClosed Circuit Piston PumpTool Capacity777 Litres max @ 2750 rpm 20 USG max @ 2750 rpmTool Pressure320 Bar maxOil Tank Capacity25 Litres / 7 USGOperating Oil Quantity35 Litres / 9 USGFrequency2.4 GhzRange Signal150m / 492'	Services	Gear Pump
Controls Closed Circuit Piston Pump Tool Capacity 77 Litres max @ 2750 rpm 20 USG max @ 2750 rpm Tool Pressure 320 Bar max Oil Tank Capacity 25 Litres / 7 USG Operating Oil Quantity 35 Litres / 9 USG Controls Brand Scanreco Frequency 2.4 Ghz Range Signal 150m / 492'	Services Capacity	
Tool Capacity 77 Litres max @ 2750 rpm 20 USG max @ 2750 rpm Tool Pressure 320 Bar max Oil Tank Capacity 25 Litres / 7 USG Operating Oil Quantity 35 Litres / 9 USG Controls Brand Scanreco Frequency 2.4 Ghz Range Signal 150m / 492'	Services Pressure	200Barmax
Iool Capacity 20 USG max @ 2750 rpm Tool Pressure 320 Bar max Oil Tank Capacity 25 Litres / 7 USG Operating Oil Quantity 35 Litres / 9 USG Controls	Tool	Closed Circuit Piston Pump
Oil Tank Capacity 25 Litres / 7 USG Operating Oil Quantity 35 Litres / 9 USG Controls Brand Scanreco Frequency 2.4 Ghz Range Signal 150m / 492'	Tool Capacity	* '
Operating Oil Quantity 35 Litres / 9 USG Controls Brand Scanreco Frequency 2.4 Ghz Range Signal 150m / 492'	Tool Pressure	320 Bar max
Controls Brand Scanreco Frequency 2.4 Ghz Range Signal 150m / 492'	Oil Tank Capacity	25 Litres / 7 USG
Brand Scanneco Frequency 2.4 Ghz Range Signal 150m / 492'	Operating Oil Quantity	35 Litres / 9 USG
Frequency 2.4 Ghz Range Signal 150m / 492'	Controls	
Range Signal 150m / 492'	Brand	Scanreco
	Frequency	2.4 Ghz
Battery Rechargeable	Range Signal	150m/492'
	Battery	Rechargeable




Working range All Flailbot models have an impressive working range of 150m (492').





1370/54"



1670 / 65 ¾"