

# Pro-Saw Loader Frame

A convenient choice for farmers and contractors wishing to utilise their front loaders for hedge and tree cutting.

All Pro-Saw attachments have protection for over speed and pressure to ensure safety.

## Key Features

- Options of hydraulic breakout, or manual breakout.
- Hydraulic head angling option, or manual turnbuckle.
- Range of fitting brackets for most loaders and telehandlers.
- LH or RH build options.
- Built in flow divider for hydraulic safety protection.



## Product Specification

	For Tractor Loader	For Telehandler
Pro-Saw Loader Frame	HRF2800	HRF3300
Reach with Pro-Saw	2.2m	2.5m
Transport Width	2.0m	2.2m
Required Hydraulic Connections	1x Double	1x Double
Weight	179kg	193kg
Pro-Saw Technical Data	1500	2000
Working Width	1.5m	2.0m
No. of Saw Blades with Tungsten Carbide Teeth	3 pcs Ø 490 mm	4 pcs Ø 490 mm
Requires Hydraulic Connections	1 x Single Acting, 1 x Return, 1 x Drain	1 x Single Acting, 1 x Return, 1 x Drain
Oil Flow	40 L/min / Max 200 bar	—
Max Branch Thickness	120mm	160mm
Continuous Duty Motor	14 Kw	—
Motor Option 1: 28cc / Required Oil Flow	—	85 L/min / Max 150 bar
Motor Option 2: 15cc / Required Oil Flow	—	50 L/min / Max 180 bar
Working Speed	5 km/h	5 km/h
Weight	130 kg	210 kg



**Want to know more about the Pro-Saw Loader Frame range?**

Scan the QR code with a smart phone or tablet to instantly view the page.