

Raptor

The new Raptor verge mower is the ideal choice for users who have a dedicated shoulder mowing operation to perform.

The Raptor can be front mounted allowing the fitting of a Bomford arm mower on the rear giving a 3.5m cut, in one pass. The Raptor can effortlessly work around street furniture and varying ground levels.

Key Features

- Cutting widths of 1.2, 1.6 or 2.0m.
- Front or rear mounted options
- Banks cutting between 90° up and 50° down
- Cat 11 three point linkage



Want to know more about the Raptor range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard ○ Optional — Not Available

Raptor	1200	1600	2000
Reach	2.84m / 9'4"	3.24m / 10'7"	3.64m / 12"
Cutting Width	1.2m / 4'	1.6m / 5'3"	2m / 6'6"
Max Offset	750mm / 2'6"	750mm / 2'6"	750mm / 2'6"
No. of Flails	32	44	54
PTO Speed (rpm)	1000 / 540	1000 / 540	1000 / 540
Cowl Angle Movement	140° (+90° to -50°)	140° (+90° to -50°)	140° (+90° to -50°)
Power Requirement	40hp	45hp	70hp
Weight	620kg / 1367lbs	830kg / 1830lbs	900kg / 1984lbs
Front Mountable	○	○	○

Offset verge mower

Complete working width can be achieved outside the tractor wheel.



Hydraulic offset

Fully operated from within the tractor cab.



Transport position

Safe transport position within the tractor width, with safety lock



Front mount option

3 sizes, available in either front/rear mount option.