

# Tri-Wing

A flex mower specifically designed for large open spaces, with wide-angle constant velocity drive shafts and in-line slip clutch protection.

The clean lines of this robust design, reduces the build up cut debris from collecting and rotting the machine deck, maximising it's working life.

Fitted with six 200/60 - 14.5 10 ply tyres as standard, the Tri-Wing 4.6 and 6m can also be supplied with an eight wheel option for reduced ground pressure. The hydro-suspension shock absorbing mechanism ensures a smooth ride and reduces stress within the mainframe.

## Key Features

- 4.6m and 6m cutting widths
- Walking wheel kit option
- Nine heavy duty updraft blades
- Choice of 5 blade configurations
- Shredder option for maize
- Hydro-suspension system
- Hydraulic level lift system



**Want to know more about the Tri-Wing range?**

Scan the QR code with a smart phone or tablet to instantly view the page.





# Product Specification

Tri-Wing	TW4600	TW6000
Cutting Width	4.60m / 15'	6.00m / 20'
Overall Width	4.75m / 15'7"	6.30m / 20'8"
Overall Length	4.9m / 16'4"	5.5m / 18'1"
Transport Width	2.5m / 8'2"	2.4m / 7'10"
Cutting Height	13mm - 393mm / 1/2" - 15"	13mm - 393mm / 1/2" - 15"
Horsepower (min)	80hp	100hp
Tip Speed	80 m/s	80 m/s
PTO Speed	1000	1000
Wing Flex (Degrees)	107° up - 21° down	109° up - 10° down
Weight (Approx)	2385kg / 5258lbs	2775kg / 6117lbs



**Road lights**  
High speed road lighting and licence plate brackets.



**Axle options**  
6, 8 and walking axle wheel options available for contour following operation.



**Contoured decks**  
Allows quick cleaning of cut material from deck surface.



**Easy to transport**  
Simple single operation to fold and travel, with additional locking pins for road transit.



**Blade options**  
We supply a range of blade options for Tri-Wing.