

Raptor

The new Raptor verge mower is the ideal choice for users who have a dedicated shoulder mowing operation to perform.

The Raptor can be front mounted allowing the fitting of a Bomford arm mower on the rear giving a 3.5m cut, in one pass. The Raptor can effortlessly work around street furniture and varying ground levels.

Key Features

- Cutting widths of 1.2, 1.6 or 2.0m
- Front or rear mounted options
- Banks cutting between 90° up and 50° down
- Cat 11 three point linkage
- Flail option - MP44 Boot Flail or Twisted Shackles



Want to know more about the Raptor range?

Scan the QR code with a smart phone or tablet to instantly view the page.



Product Specification

● Standard ○ Optional — Not Available

| Raptor | 1200 | 1600 | 2000 |
|---------------------|---------------------|---------------------|---------------------|
| Reach | 2.84m / 9'4" | 3.24m / 10'7" | 3.64m / 12" |
| Cutting Width | 1.2m / 4' | 1.6m / 5'3" | 2m / 6'6" |
| Max Offset | 750mm / 2'6" | 750mm / 2'6" | 750mm / 2'6" |
| No. of Flails | 32 | 44 | 54 |
| PTO Speed (rpm) | 1000 / 540 | 1000 / 540 | 1000 / 540 |
| Cowl Angle Movement | 140° (+90° to -50°) | 140° (+90° to -50°) | 140° (+90° to -50°) |
| Power Requirement | 40hp | 45hp | 70hp |
| Weight | 620kg / 1367lbs | 830kg / 1830lbs | 900kg / 1984lbs |
| Front Mountable | ○ | ○ | ○ |



Offset verge mower

Complete working width can be achieved outside the tractor wheel.



Hydraulic offset

Fully operated from within the tractor cab.



Transport position

Safe transport position within the tractor width, with safety lock



Front mount option

3 sizes, available in either front/rear mount option.